



## Introduction

The iVectorOne API allows customers to integrate with a large number of different suppliers via a single API. It is organised around REST with predictable resource-oriented URLs, accepts form-encoded request bodies, returns JSON-encoded responses, and uses standard HTTP response codes, authentication, and verbs.

## Accounts

iVectorOne users will be provided with two accounts: Test and Production. The Test account should only be used during the development phase to test your integration and validate your supplier connections. Bookings created in one account cannot be moved to another account.

## Authentication

Authentication to the API is performed via HTTP Basic Auth. You will be provided with a different username and password for each account. The credentials you use to authenticate the request determines whether the request is routed to the Test or Production account.

All API requests must be made over HTTPS. Calls made over plain HTTP will fail. API requests without authentication will also fail.

## Message Formats

Requests are sent as JSON or in some cases form-encoded. String properties are encoded using UTF-8, and date properties are represented by ISO 8601 strings.

## Errors

iVectorOne uses conventional HTTP response codes to indicate the success or failure of an API request. In general: Codes in the 2xx range indicate success. Codes in the 4xx range indicate an error that failed given the information provided (e.g., a required parameter was omitted, etc.). Codes in the 5xx range indicate an error with iVectorOne servers (these are rare).



Code	Reason
400 - Bad Request	The request was unacceptable, often due to missing a required parameter.
401 - Unauthorised	No valid username and / or password provided
500, 502, 503, 504 - Server Errors	Something went wrong on the iVectorOne end. (These are rare.)

## Versioning

The API base URL contains a version identifier. The current version is **V2**.

Whenever we make a backwards-incompatible change to a general availability, non-beta product, we release a new API version to avoid causing breakages for existing developers. You can then continue to use the old API version, or update your application to upgrade to the new API version. APIs for beta products are subject to breaking changes without versioning.

We consider the following changes to be backwards compatible:

- Adding new API endpoints
- Adding new optional parameters to existing endpoints
- Adding new data elements to existing response schemas
- Adding new enum values, including `error_types` and `error_codes`
- Changing the length or format of opaque strings, such as object IDs, error messages, and other human-readable strings.

## Postman collection

The Postman collection is a convenient tool for exploring iVectorOne API endpoints without writing code. The Postman collection provides pre-formatted requests for almost all of iVectorOne API endpoints. All you have to do is fill in your authentication and any arguments.

To get started, check out the iVectorOne Postman Collection

<https://documenter.getpostman.com/view/19225969/VUjQmjqT>

## Support

For help and support during your integration, please email the support team and we'll do our best to assist. [helpdesk@ivectorone.com](mailto:helpdesk@ivectorone.com)



## API Reference

### Base URL

Each API call has its own REST path relative to the base Url, eg. [Base Url]/property/search.

<https://api.ivectorone.com/v2>

### Property List

Retrieve a list of properties

#### Request

GET [Base URL]/properties

#### Parameters

Query Parameter	Data Type	Description
suppliers	String ?	Optional comma-separated list of supplier names to list properties for. If blank all properties will be returned.
lastmodified	Date?	Optional parameter to filter properties to only those modified after a certain date.

#### Response

Node	Data Type	Description
PropertyListResponse		
Properties	List ?	The list of properties.
PropertyID	Integer	The unique identifier of the property. This can be used in the GetPropertyContent call to get full content.



## Property Content

Retrieve the full content for specified properties. Includes the content for every third party supplier mapped to that property.

### Request

**GET** [Base URL]/properties

### Parameters

Parameter	Data Type	Description
propertyids	String	Comma-separated list of property ids to return content for. This is limited to 500 property ids per request for performance reasons.

### Response

Parameter	Data Type	Description
PropertyContentResponse		
Properties	List ?	The list of properties.
PropertyID	Integer	The unique identifier of the property.
TTICode	string	The TTI code identifying the property
SupplierContent	List	A list of supplier-specific content for the property.
SupplierContent	Single	
PropertyName	String	The name of the property.
Supplier	String	The name of the supplier
SupplierPropertyReference	String	The supplier's reference for the property
Address	Single	The property Address
AddressLine1	String	The first line of the address
AddressLine2	String ?	The second line of the address



TownOrCity	String	The town or city name
CountyOrState	String ?	The county or state name
PostCodeOrZip	String	The postcode or Zip code
Telephone	String	The telephone number
Geography	Single	
Country	String	The name of the country the property is in.
Region	String	The name of the region the property is in.
Resort	String	The name of the resort the property is in.
Latitude	Decimal	The latitude of the property.
Longitude	Decimal	The longitude of the property.
Code	String	The geography code of the property.
Rating	String	The star rating of the property.
Description	String	The description of the property
Facilities	List ?	A list of facilities that the property provides
Facility	String	The name of the facility
MainImageURL	String	The URL of the main image
Images	List ?	A list of Image URLs
ImageURL	String	
ContentVariables	List?	A list of content variables
ParentGroupKey	Int	A parent group of the content variable(Distance = 1, Distances= 2, km=3, AccommodationTypes=4,AccommodationType=5)
Group	Int	A group of the content variable (Distance = 1, Distances= 2, km=3, AccommodationTypes=4,AccommodationType=5)
SubGroup	String?	A subgroup of the content variable
Key	String	A subtype of group i.e. AccomodationType
Value	String	A value of subtype i.e. Hotel
Units	Int	A number of units



## Search

Retrieve the availability for specified properties.

## Request

GET [Base URL]/properties/search

## Parameters

Parameter	Data Type	Description
PropertySearchRequest		
ArrivalDate	Date	The first stay date.
Duration	Integer	The length of the stay.
Properties	Integer List	CSV of unique identifiers of the properties to search.
Rooms	List	<p>Pipe separated room pax combinations</p> <ul style="list-style-type: none"> <li>- (adults,children,infants~child ages)</li> <li>- adults - integer, each room must have at least one</li> <li>- children - integer</li> <li>- Infants - integer</li> <li>- Child ages - csv of integer, total must match # of children (infant ages don't need to specified)</li> </ul> <p>E.g. rooms=(1,1,1~7) (2,0,0)</p> <ul style="list-style-type: none"> <li>- Is a 2-room search</li> <li>- Room 1 - 1 Adult, 1 child, 1 infant, aged 7(child)</li> <li>- Room 2 - 2 Adults</li> </ul>
NationalityID	String?	The lead guest nationality ID using ISO 3166-2 country code
Currency code	String?	The ISO 4217 currency code. (Default is set to GBP)
OpaqueRates	String?	A boolean indicating whether opaque rates are supported (Default false)
SellingCountry	String?	The selling country using ISO 3166-2 country code
Suppliers	String?	The supplier(s) to search
DedupeMethod	String?	The method of which the results will be deduped by, either "cheapestleadin", which selects property results from the supplier with the cheapest room cost for that property, or "none", which selects all property results from the supplier and



		does not dedupe
--	--	-----------------

## Response

Parameter	Data Type	Description
PropertySearchResponse		
PropertyResults	List ?	The property search results.
PropertyResult	Single	
BookingToken	String	Stores information needed to book the result. Must be passed into the pre-book request.
PropertyID	Integer	Unique property identifier.
RoomTypes	List	List of bookable room results.
RoomType	Single	
RoomID	Integer	Unique identifier of the rooms in the order they were specified in the request.
RoomBookingToken	String	Stores information needed to book the room result. Must be passed into the pre-book request.
SupplierReference1	String	Room Token returned from the third party. Must be passed into the pre-book request
SupplierReference2	String	Room Token returned from the third party. Must be passed into the pre-book request
Supplier	String	The name of the supplier.
MealBasisCode	String	Unique identifier of the meal basis.
RoomType	String	The name of the room type.
RoomTypeCode	String	The code of the room type.
SupplierRoomType	String	The supplier's name for the room type.
CurrencyCode	String	The ISO code of the currency.
TotalCost	Decimal	The total cost of the room.
Discount	Decimal	The discount for the room.
NonRefundable	Boolean	Determines whether the room is refundable.



RateCode	String	The rate code for the room.
CancellationTerms	List ?	The cancellation terms for the room, if supported at search.
CancellationTerm	Single	
StartDate	Date	The start date of the cancellation policy.
EndDate	Date	The end date of the cancellation policy.
Amount	Decimal	The cancellation cost.
Adjustments	List?	The adjustment terms for the room, if supported at search.
AdjustmentType	String	The adjustment type. Possible values: Supplement, Offer, Tax
AdjustmentName	String	The name of the adjustment
AdjustmentAmount	Decimal	The amount of the adjustment
Description	String	The description of the adjustment
CommissionPercentage	Decimal?	The commission percentage of the room type
OnRequest	Boolean?	Determines whether room is on request
GrossCost	Decimal?	The gross cost of the room type. Only returned if different than the amount and not 0.

## Pre-book

Confirm the availability and price for specified properties.

## Request

**POST** [Base URL]/properties/prebook

## Parameters

Parameter	Data Type	Description
PropertyPrebookRequest		
BookingToken	String	Taken from a property result in the property search response.
RoomBookings	List	A list of room search results to pre-book.



RoomBooking	Single	
RoomBookingToken	String	Taken from a room result in the property search response.
SupplierReference1	String	Taken from a room result in the property search response.
SupplierReference2	String	Taken from a room result in the property search response.
Nationality ID	String?	The customer nationality ID using ISO 3166-2 country code
OpaqueRates	String?	A boolean indicating whether opaque rates are supported (Default false)
SellingCountry	String?	The source market country using ISO 3166-2 country code

## Response

Parameter	Data Type	Description
PropertyPrebookResponse		
BookingToken	String	Stores information needed to book the result. Must be passed into the book request.
SupplierReference1	String	Property level Token returned from the third party. Must be passed into the book request if returned at prebook.
SupplierReference2	String	Property level Token returned from the third party. Must be passed into the book request if returned at prebook.
TotalCost	Decimal	The total price of the property booking.
RoomBookings	List	
RoomBooking	Single	
Supplier	String	The name of the supplier
TotalCost	Decimal	The total cost for the room.
RoomBookingToken	String	Stores information needed to book the result. Must be passed into the book request.
SupplierReference	String	Room level Token returned from the third party. Must be passed into the book request
CancellationTerms	List ?	The cancellation terms for the property booking.
CancellationTerm	Single	
StartDate	Date	The start date of the cancellation policy.



EndDate	Date	The end date of the cancellation policy.
Amount	Decimal	The cancellation cost.
Errata	List ?	
Erratum	String	Any notes relevant to the customer before booking (eg. regional taxes apply, facilities not available, etc)

## Book

Finalise and confirm a booking for specified properties.

### Request

POST [Base URL]/properties/book

### Parameters

Parameter	Data Type	Description
PropertyBookRequest		
BookingToken	String	Taken from the property pre-book response
BookingReference	String	Unique reference to be passed to the third party to identify the booking in their system (if supported)
SupplierReference1	String	Taken from the property pre-book response, must be passed in if returned at pre-book.
SupplierReference2	String	Taken from the property pre-book response, must be passed in if returned at pre-book.
RoomBookings	List	A list of room pre-book results to book
RoomBooking	Single	
RoomBookingToken	String	Taken from a room result in the property search response
SpecialRequest	String?	Any special request for the room
SupplierReference	String	Taken from the property pre-book response
GuestDetails	List	The details of all the guests on the booking
GuestDetail	Single	



Type	String	Must be one of "Adult", "Child" or "Infant"
Title	String	The guest's title, eg. Mr, Mrs.
FirstName	String	The guest's first name.
LastName	String	The guest's last name.
DateOfBirth	Date	The guest's date of birth.
LeadCustomer	Single	The details of the lead customer
CustomerTitle	String	
CustomerFirstName	String	
CustomerLastName	String	
DateOfBirth	Date	
CustomerAddress1	String	
CustomerAddress2	String?	
CustomerTownCity	String	
CustomerCounty	String	
CustomerPostcode	String	
CustomerBookingCountryCode	String	ISO Alpha-2 code
CustomerPhone	String?	
CustomerMobile	String?	
CustomerEmail	String?	
PassportNumber	String?	
NationalityID	String?	The customer nationality ID using ISO 3166-2 country code
OpaqueRates	String?	A boolean indicating whether opaque rates are supported (Default false)
SellingCountry	String?	The source market country using ISO 3166-2 country code

## Response

Parameter	Data Type	Description
PropertyBookResponse		
SupplierBookingReference	String	The supplier's unique identifier of the booking.



SupplierReference1	String	Token returned from the third party. Must be passed into the cancel request if returned at book.
SupplierReference2	String	Token returned from the third party. Must be passed into the cancel request if returned at book.
BookingToken	String	Stores information needed to book the result. Must be passed into the book request.

## Pre-Cancel

Pre-cancel a confirmed booking, returns the cancellation cost

### Request

POST [Base URL]/properties/precancel

### Parameters

Parameter	Data Type	Description
PropertyPreCancelRequest		
SupplierBookingReference	String	The supplier's booking reference returned in the property book response
BookingToken	String	Stores information needed to book the result. Must be passed into the book request.
SupplierReference1	String	Token returned from the third party. Must be passed into the cancel request if returned at book.
SupplierReference2	String	Token returned from the third party. Must be passed into the cancel request if returned at book.

### Response

Parameter	Data Type	Description
PropertyPreCancelResponse		



Amount	Decimal	The amount to cancel the booking.
CurrencyCode	String	The ISO code of the currency.

## Cancel

Cancel a confirmed booking

### Request

**POST** [Base URL]/properties/cancel

### Parameters

Parameter	Data Type	Description
PropertyCancelRequest		
SupplierBookingReference	String	The supplier's booking reference returned in the property book response
SupplierReference1	String	Token returned from the third party. Must be passed into the cancel request if returned at book.
SupplierReference2	String	Token returned from the third party. Must be passed into the cancel request if returned at book.
BookingToken	String	Stores information needed to book the result. Must be passed into the book request.

### Response

Parameter	Data Type	Description
PropertyCancelResponse		
SupplierCancellationReference	String	The supplier's unique reference for the cancellation if returned otherwise supplier booking reference